



Recommended graphics boards for RadiForce monitors

To get the most out of the extraordinary capabilities of our high-definition RadiForce monitors, we recommend that you use them with one of EIZO's validated MED-XN graphics boards. These are based on NVIDIA Quadro graphics boards and are optimised in terms of drivers and BIOS to meet the specific requirements for driving EIZO RadiForce monitor solutions. In addition, it is also possible to run up to four screens simultaneously with a single graphics board. EIZO offers technical support and guaranteed service for all boards.

Your advantages at a glance

Outstanding clarity and security

Manufacturer recommendation for combining EIZO RadiForce monitor model and MED-XN graphics board validated by EIZO guarantees correct functionality, performance suited to the specific task and full compatibility.

Excellent image quality

Images are displayed in a grey level depth of up to 10-bit.

Native Image Display

Interpolating driver functionalities (such as dithering) and colour management options are deactivated to ensure a reliable diagnosis.

High investment security

Significantly longer product life cycles, a high availability strategy and very stable prices are an asset when it comes to long-term projects.

Customer-oriented service

- ✔ Free technical support for monitors, RadiCS QA software and boards from under one roof
- ✔ Free logistical onsite replacement service for defective EIZO medical boards within the warranty period (in Belgium, Germany, Italy, Austria, the Netherlands and Switzerland)
- ✔ Digital serial numbers contained on the graphics board BIOS allow serial numbers for acceptance and consistency testing protocols to be automatically read via RadiCS. Documentation requirements in accordance with DIN 6868-157



MED-XN92



MED-XN72



MED-XN51LP

Bus Interface	PCI Express 3.0 x16	PCI Express 3.0 x16	PCI Express 3.0 x16
Compatible OS	Windows 10	Windows 10	Windows 10, Windows 8.1, Windows 7 (four output max)
Frame Buffer Memory	8 GB GDDR6	5 GB GDDR5X	4 GB GDDR5
Display Colors / Grayscale Tones	10-bit, 8-bit	10-bit, 8-bit	10-bit, 8-bit
Output Terminals	DisplayPort x 3 USB-C x 1	DisplayPort x 4	4x Mini DisplayPort
Cable	1x cable (DisplayPort – DVI-D)	1x cable (DisplayPort – DVI-D)	2x cable (Mini DisplayPort – DisplayPort) 1x cable (Mini DisplayPort – DVI-D)
Daisy Chain Support	Yes	Yes	Yes
Maximum Power Consumption	160 W, PCIe 8-pin power connector required	75 W	47 W
Chassis	Standard	Standard	Low-Profile
Dimensions (W x H)	241.3 x 111.2 mm	200.7 x 111.2 mm	153.9 x 68.9 mm
Warranty	3 years on-site exchange service Optional: 5 years on-site exchange service	3 years on-site exchange service Optional: 5 years on-site exchange service	3 years on-site exchange service Optional: 5 years on-site exchange service
RX1270	★	✓	✓
RX850	★	✓	✓
RX660	✓	★	✓
RX560-MD	★	✓	✓
RX370	✓	★	✓
RX250	✓	✓	★
GX560-MD	★	✓	✓
GX340	✓	★	✓
GX240	✓	✓	★
MX315W	✓	★	✓
MX216-HB	✓	✓	★
MX243W	✓	✓	★
MX216-SB	✓	✓	★
MX194	✓	✓	★
MS236WT-A	✓	✓	★

✓ *Compatible*

★ *Recommended*

Graphics board compatibility is subject to change without notice. Please check EIZO website for updates.

Find your local sales partners or EIZO contact persons: eizo.eu/contact

Copyright © 2022 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany.
All rights, errors and modifications are subject to change. Last updated: October 2022

